

CM-60

Corrugated Rubber Matting

Corrugated Rubber Matting is the material of choice for enhanced floor safety and surface protection. It is manufactured with a V-Ribbed surface texture which improves foot traction and minimizes cleanup by trapping water, dirt and debris. It features an all-weather and water resistant rubber composition for increased matting service life.

- Backside includes a Fabric-Finish feature, Improving Floor Grip
- Thicknesses: 1/8", 1/4", 3/8", 1/2"
- Custom Widths Available
- Best suited for the following applications:
 - Construction Work Areas
 - Heavy - Traffic Walkways
 - Surface Protection
 - Tool Drawer Liners
 - Garages

Properties	Test Method	Typical Values
Tensile	ASTM D412	500 psi
Elongation	ASTM D412	180%
Shore "A" Durometer	ASTM D2240	70 ± 5
Temperature Range	Fahrenheit (°F)	-40 to +176
Color	Visual	Black
Finish	Visual	Corrugated Top / Fabric Finish Back

**Standard RMA tolerances apply*

Availability:

- Custom Widths
- Continuous Roll Lengths

The information supplied herein is based upon information currently available on the subject. The above values are typical properties and should be used only as a guide. There are no warranties, either expressed or implied, including the warranty for fitness of use or of merchantability. It is up to the end user to determine whether the material is appropriate for the intended application.