

## ARP-CG-40

### Commercial Grade Silicone Sheet

**Features:**

- Low Compression Set
- Outstanding Resistance to UV, Ozone, Oxidation and Weathering
- Resistance at Extreme High and Low Temperatures
- Good Chemical Resistance

Properties	Test Method	Typical Values
<b>Color</b>	Visual	Red, Grey, Black
<b>Finish</b>	Visual	Smooth
<b>Width</b>	ASTM D751	36" – 60"
<b>Thickness</b>	ASTM D751	.010" – 1"
<b>Shore "A" Durometer</b>	ASTM D2240	40 ± 5
<b>Tensile Strength, psi</b>	ASTM D412	600
<b>Elongation, %</b>	ASTM D412	400
<b>Tear Strength, ppi Die "B"</b>	ASTM D624	85
<b>Temperature Range</b>	Fahrenheit (°F)	-76 to +450

\*The values from samples of different sizes will be different from that stated here

**Availability:**

- Custom Widths
- Continuous Roll Lengths
- Color Match Capabilities
- Pressure Sensitive Adhesive (PSA) Backing

---

The information supplied herein is based upon information currently available on the subject. The above values are typical properties and should be used only as a guide. There are no warranties, either expressed or implied, including the warranty for fitness of use or of merchantability. It is up to the end user to determine whether the material is appropriate for the intended application.